

Klübersynth J 44-402

Special synthetic grease for ball joints in chassis components



Benefits for your application

- **Low breakaway and running torques even after 24 hours of inoperative position**
 - avoidance of cracking and stick-slip noise
- **Particularly low friction values**
 - smooth running of joints even with high torsion
- **Good low-temperature behaviour**
 - consistent smooth operation

Description

Klübersynth J 44-402 consists of fully synthetic base oil, lithium soap and additives increasing the ageing resistance and the corrosion protection of steel surfaces. Special additives increase adhesion on steel and plastic components, improve the dampening effect between the friction bodies and reduce the breakaway and running torques in ball joints. Klübersynth J 44-402 has been designed to reduce slick-slip and to keep friction values and the difference between static and dynamic friction as low as possible. The usual seal materials like chlorobutadiene rubber (CR) were taken into consideration when developing the grease. Prior to series application we recommend testing the compatibility with the elastomers and plastics used.

tilting and slewing motions. Klübersynth J 44-402 was developed and tested in cooperation with renowned car manufacturers.

Application notes

Klübersynth J 44-402 can be applied by brush, spatula, grease gun, automatic metering systems and central lubrication systems.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Application

Klübersynth J 44-402 is used for sealed joints in e.g. stabilizers, transverse links and wheel joints in the car industry. The grease has been tested in steel/POM pairings subject to oscillating

Pack sizes	Klübersynth J 44-402
Can 1 kg	-
Bucket 25 kg	-
Drum 180 kg	-

Product data	Klübersynth J 44-402
Article number	004263
Lower service temperature	-40 °C / -40 °F
Upper service temperature	130 °C / 266 °F
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 360 mm ² /s
Chemical composition, thickener	lithium soap
Chemical composition, type of oil	synthetic hydrocarbon oil



Klübersynth J 44-402

Special synthetic grease for ball joints in chassis components

Product data	Klübersynth J 44-402
Density at 20 °C	approx. 0.90 g/cm ³
Colour space	beige
Flow pressure of lubricating greases, DIN 51805, test temperature: -40 °C	<= 1 400 mbar
NLGI grade, DIN 51818	2
Corrosion inhibiting properties of lubricating greases, DIN 51802, (SKF-EMCOR), test duration: 1 week, distilled water	<= 1 corrosion degree
Drop point, DIN ISO 2176, IP 396	>= 185 °C
Water resistance, DIN 51807 pt. 01, 3 h/90 °C, rating	1 - 90
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

Klüber Lubrication München SE & Co. KG / Geisenhausenerstraße 7 / 81379 München / Germany / phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.